

HDS STATIONNAIRE - NG

SPÉCIFICATIONS TECHNIQUES

Modèle	Référence	gpm	psi	Entraînement	CV	Électrique	Amps	Pompe	Poids de l'emballage (lb)	BTU	Dimensions de l'emballage (L x l x H) po
Conception d'armoire moyenne, chauffé au gaz naturel 3,5 à 5,0 gpm											
HDS 3.5/20 Ea ST NG	1.109-715.0	3,5	2000	Belt	5	230 V / 1 ph	25	KD4020R / 1350	815	320 000	49 x 24 x 48
HDS 4.0/22 Ea ST NG	1.109-716.0	4	2200	Belt	6,2	230 V / 1 ph	29	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eb ST NG	1.109-717.0	4	2200	Belt	6,2	230 V / 3 ph	16	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Ef ST NG	1.109-719.0	4	2200	Belt	6,2	575 V / 3 ph	6,5	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eg ST NG	1.109-720.0	4	2200	Belt	6,2	208 V / 1 ph	30	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eh ST NG	1.109-721.0	4	2200	Belt	6,2	208 V / 3 ph	18	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 3.9/30 Ea ST NG	1.109-723.0	3,9	3000	Belt	8,2	230 V / 1 ph	36	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eb ST NG	1.109-724.0	3,9	3000	Belt	8,2	230 V / 3 ph	25	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Ef ST NG	1.109-726.0	3,9	3000	Belt	8,2	575 V / 3 ph	14	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eg ST NG	1.109-727.0	3,9	3000	Belt	8,2	208 V / 1 ph	38	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eh ST NG	1.109-728.0	3,9	3000	Belt	8,2	208 V / 3 ph	27	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 5.0/23 Ea ST NG	1.109-730.0	5,0	2300	Belt	8,2	230 V / 1 ph	36	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eb ST NG	1.109-731.0	5,0	2300	Belt	8,2	230 V / 3 ph	25	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Ef ST NG	1.109-733.0	5,0	2300	Belt	8,2	575 V / 3 ph	14	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eg ST NG	1.109-734.0	5,0	2300	Belt	8,2	208 V / 1 ph	38	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eh ST NG	1.109-735.0	5,0	2300	Belt	8,2	208 V / 3 ph	27	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 4.8/30 Ea ST NG	1.109-736.0	4,8	3000	Belt	10	230 V / 1 ph	42	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eb ST NG	1.109-737.0	4,8	3000	Belt	10	230 V / 3 ph	26	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Ef ST NG	1.109-739.0	4,8	3000	Belt	10	575 V / 3 ph	14	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eg ST NG	1.109-740.0	4,8	3000	Belt	10	208 V / 1 ph	49	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eh ST NG	1.109-741.0	4,8	3000	Belt	10	208 V / 3 ph	32	KT6035R / 1225	885	415 000	49 x 24 x 48

SPÉCIFICATIONS TECHNIQUES

Modèle	Référence	gpm	psi	Entraînement	CV	Électrique	Amps	Pompe	Poids de l'emballage (lb)	BTU	Dimensions de l'emballage (L x l x H) po
Conception de grande armoire, chauffé au gaz naturel 6,3+ gpm											
HDS 6.3/32 Eb ST NG	1.109-744.0	6,3	3200	Belt	15	230 V / 3 ph	39	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 6.3/32 Ef ST NG	1.109-746.0	6,3	3200	Belt	15	575 V / 3 ph	18	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 6.3/32 Eh ST NG	1.109-747.0	6,3	3200	Belt	15	208 V / 3 ph	39	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 8.0/32 Eb ST NG	1.109-748.0	8,0	3200	Belt	20	230 V / 3 ph	46	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 8.0/32 Ef ST NG	1.109-750.0	8,0	3200	Belt	20	575 V / 3 ph	21	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 8.0/32 Eh ST NG	1.109-751.0	8,0	3200	Belt	20	208 V / 3 ph	60	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 9.5/30 Eb ST NG	1.109-752.0	9,5	3000	Belt	20	230 V / 3 ph	52	KX1036R / 1650	1910	816 000	64 x 35 x 61
HDS 9.5/30 Ef ST NG	1.109-754.0	9,5	3000	Belt	20	575 V / 3 ph	21	KX1036R / 1650	1910	816 000	64 x 35 x 61
HDS 9.5/30 Eh ST NG	1.109-755.0	9,5	3000	Belt	20	208 V / 3 ph	30	KX1036R / 1650	1910	816 000	64 x 35 x 61