

HDS STATIONNAIRE - LP

SPÉCIFICATIONS TECHNIQUES

Modèle	Référence	gpm	psi	Entraînement	CV	Électrique	Amps	Pompe	Poids de l'emballage (lb)	BTU	Dimensions de l'emballage (L x l x H) po
Conception d'armoire moyenne, chauffé au gaz liquéfié 3,5 à 5,0 gpm											
HDS 3.5/20 Ea ST LP	1.109-756.0	3,5	2000	Belt	5	230 V / 1 ph	25	KD4020R / 1350 h	815	320 000	49 x 24 x 48
HDS 4.0/22 Ea ST LP	1.109-757.0	4	2200	Belt	6,2	230 V / 1 ph	29	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eb ST LP	1.109-758.0	4	2200	Belt	6,2	230 V / 3 ph	16	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Ef ST LP	1.109-760.0	4	2200	Belt	6,2	575 V / 3 ph	6,5	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eg ST LP	1.109-761.0	4	2200	Belt	6,2	208 V / 1 ph	30	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 4.0/22 Eh ST LP	1.109-762.0	4	2200	Belt	6,2	208 V / 3 ph	18	KM4035R / 1250	843	364 000	49 x 24 x 48
HDS 3.9/30 Ea ST LP	1.109-764.0	3,9	3000	Belt	8,2	230 V / 1 ph	36	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eb ST LP	1.109-765.0	3,9	3000	Belt	8,2	230 V / 3 ph	25	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Ef ST LP	1.109-767.0	3,9	3000	Belt	8,2	575 V / 3 ph	14	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eg ST LP	1.109-768.0	3,9	3000	Belt	8,2	208 V / 1 ph	38	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 3.9/30 Eh ST LP	1.109-769.0	3,9	3000	Belt	8,2	208 V / 3 ph	27	KM4035R / 1225	856	354 000	49 x 24 x 48
HDS 5.0/23 Ea ST LP	1.109-771.0	5,0	2300	Belt	8,2	230 V / 1 ph	36	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eb ST LP	1.109-772.0	5,0	2300	Belt	8,2	230 V / 3 ph	25	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Ef ST LP	1.109-774.0	5,0	2300	Belt	8,2	575 V / 3 ph	14	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eg ST LP	1.109-775.0	5,0	2300	Belt	8,2	208 V / 1 ph	38	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 5.0/23 Eh ST LP	1.109-776.0	5,0	2300	Belt	8,2	208 V / 3 ph	27	KT6035R / 1225	856	439 000	49 x 24 x 48
HDS 4.8/30 Ea ST LP	1.109-777.0	4,8	3000	Belt	10	230 V / 1 ph	42	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eb ST LP	1.109-778.0	4,8	3000	Belt	10	230 V / 3 ph	26	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Ef ST LP	1.109-780.0	4,8	3000	Belt	10	575 V / 3 ph	14	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eg ST LP	1.109-781.0	4,8	3000	Belt	10	208 V / 1 ph	49	KT6035R / 1225	885	415 000	49 x 24 x 48
HDS 4.8/30 Eh ST LP	1.109-782.0	4,8	3000	Belt	10	208 V / 3 ph	32	KT6035R / 1225	885	415 000	49 x 24 x 48

SPÉCIFICATIONS TECHNIQUES

Modèle	Référence	gpm	psi	Entraînement	CV	Électrique	Amps	Pompe	Poids de l'emballage (lb)	BTU	Dimensions de l'emballage (L x l x H) po
Conception de grande armoire, chauffé au gaz naturel 6,3+ gpm											
HDS 6.3/32 Eb ST LP	1.109-785.0	6,3	3200	Belt	15	230 V / 3 ph	39	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 6.3/32 Ef ST LP	1.109-787.0	6,3	3200	Belt	15	575 V / 3 ph	18	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 6.3/32 Eh ST LP	1.109-788.0	6,3	3200	Belt	15	208 V / 3 ph	39	KT6035R / 1625	1825	507 000	64 x 35 x 61
HDS 8.0/32 Eb ST LP	1.109-789.0	8,0	3200	Belt	20	230 V / 3 ph	46	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 8.0/32 Ef ST LP	1.109-791.0	8,0	3200	Belt	20	575 V / 3 ph	21	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 8.0/32 Eh ST LP	1.109-792.0	8,0	3200	Belt	20	208 V / 3 ph	60	KX9536R / 1458	1840	658 000	64 x 35 x 61
HDS 9.5/30 Eb ST LP	1.109-793.0	9,5	3000	Belt	20	230 V / 3 ph	52	KX1036R / 1650	1910	775 000	64 x 35 x 61
HDS 9.5/30 Ef ST LP	1.109-795.0	9,5	3000	Belt	20	575 V / 3 ph	21	KX1036R / 1650	1910	775 000	64 x 35 x 61
HDS 9.5/30 Eh ST LP	1.109-796.0	9,5	3000	Belt	20	208 V / 3 ph	60	KX1036R / 1650	1910	775 000	64 x 35 x 61